

WareMini

Max Results with Mini Effort



Your Choice, Our Commitment

WareMini

Affordable high performance for warewash applications

It's not everyday that high performance and simplicity in use can be found in a single package that's also very affordable. SEKO's new WareMini range offers digital technology enclosed in a small attractive double pump system, pre-cabled and preset. The perfect recipe for ideal warewash dosing applications. Effortlessly delivering outstanding results, this WareMini range provides the perfect balance between value and benefits.



WareMini Digital LL 1 detergent pump, 1 rinse-aid pump



WareMini Digital DL
1 solenoid pump for powder detergent, 1 rinse-aid pump



WareMini Analogue LL 1 detergent pump, 1 rinse-aid pump



WareMini Analogue DL
1 solenoid pump for powder detergent, 1 rinse-aid pump

Spotlight

Digital Models Only

- Digital LED display provides clear visibility in any lighting condition
- Seko Unit set point displayed during operation to accurately monitor wash tank conditions
- Fast, easy programming; WareMini is pre programmed for typical, average wash tank conditions
- Probe and Probeless operation settings available
- "Air" display reading: Indicates chemical feed is delayed until the probe is fully submersed in water
- Safe Mode Option; Automatically switches operation mode to a probeless setting

Features

- Turn-key system pre-cabled, ready to be connected, with no need to open and connect inside the system, reducing installation time
- Reduced inventory stock thanks to its switching (multi-voltage), power supply from 100-240Vac
- Simple hardware installation that needs no fixed power supply as powered directly through signals
- Very water resistant with a high degree of protection offered by the Nema 4X enclosure
- Designed to operate in the worst conditions with its extended conductivity range 200µS to 10mS

WashMini Digital LL

Power supply: 100 - 240 Vac

Detergent Flow Rate: 4.7 oz/min at 1.5 psi

Rinse Aid Flow Rate: 0.7 oz/min at 45 psi

WashMini Analogue LL

Power supply:	100 - 240 Vac
Detergent Flow Rate:	4.7 oz/min at 1.5 psi
Rinse Aid Flow Rate:	0.7 oz/min at 45 psi

WashMini Digital DL

Power supply:	100 - 240 Vac
Detergent:	Solenoid valve for powder detergent
Rinse Aid Flow Rate:	0.7 oz/min at 45 psi

WashMini Analogue DL

Power supply:	100 - 240 Vac
Detergent:	Solenoid valve for powder detergent
Rinse Aid Flow Rate:	0.7 oz/min at 45 psi

Your Choice, Our Commitment

In the modern Globalised world, being a privately owned Company has significant benefits especially for our Customers, our Partners. For over 40 years, SEKO has developed a Global organisation able to take the longer view, manage the pressure of the now, and to plan for the long term, delivering true Partnership for our Customers, with transparency and mutual respect for each other.

Whether it's for our reknown flexibility, our attention to detail, the high-quality products, or just the way we do business, we understand that it's Your Choice to do business with us. It is Our Commitment to fulfill your needs wherever you, our Customers are.



For more information about our portfolio, worldwide locations, approvals, certifications, and local representatives, please visit www.sekousa.com



As part of a process of on-going product development, SEKO reserves the right to amend and change specifications without prior notice. Published data may be subject to change.

